ZO





hansaequipment.com.au

Γ20 **Features and Benefits**




BUILT FOR DURABILITY

Manufactured from 304 stainless steel, the T20 is built for durability. A grit blasted and 2 pack painted chassis ensures longevity and that return on investment of the T20 outperforms expectations.



BUILT FOR COMFORT

The T20 is built for comfort and ease of use, with hydraulic drawbar suspension for the best ride possible as standard and the option of an automatic door eliminating any need to get out to adjust settings meaning a long days spreading becomes a pleasure.



PERFORMANCE AND RELIABILITY

The reliable design of the Southern Spreaders 760 chain conveyor feeds the spinners to produce a positive and consistent product feed of all materials in all conditions and terrain.

ISOBUS

Simply Plug and play, the Hansa ISOBUS control system is compatible with all ISOBUS compliant terminals and is variable rate ready as standard. This allows the operator to move the spreader from one machine to another with ease and no setup changes.



Inclusions & Options

TYRES	650/65 R30.5 floatation tyres 650/65 R30.5 twin radial high speed, high load flotation tyre	\bigcirc
TARP	900 gsm rollover tarp	0
LOAD CELLS	When selected with load ISOBUS rate controller auto dynamic calibration is enabled	0
RATE CONTROLLER	ISOBUS (auto rate calibration) Hansa H7 controller (7" Touch screen)	00
SECTION CONTROL	Twin conveyor for headland and section control (available with H7 & ISOBUS rate controllers)	0
AXLE	Tandem 150mm Square Axle Beam, with Rear Steerable Axle (track options of 2,500mm & 3,000mm)	•
BRAKES	Hydraulic	0

A full range of options are available upon request

Specifications

MAX PAYLOAD 4j9 25,000 kg

SPREAD WIDTH Urea 36m / SSP 50m

CAPACITY 20.000L

TARE WEIGHT 7.300kg

LOADING HEIGHT 3.100mm

UREA CAPACITY 15,000kg

LIME CAPACITY 25,000kg

BIN LENGTH 5.950mm

Inclusions

Optional ()

OVERALL LENGTH 8,900mm

BIN WIDTH 2,700mm

STANDARD WHEEL TRACK 3.000mm

CONVEYER WIDTH 750mm wide

OIL FLOW 160L/min

WARRANTY 12 months

Hansa provides all information in good faith, and reserves all rights to alter/change specifications without notice. Purchasers must conduct their own enquiries to ensure that the products are suitable for their own particular purposes as all information is provided as an approximation and are to be used as a guide only. Photographs may show aftermarket or optional equipment that is available at extra cost. Hansa Precision Equipment Pty Ltd. Copyright 2022. ABN: 74 604 073 350

139 Learmonth St, Alfredton VIC sales@hansaequipment.com.au hansaequipment.com.au

