

T12



hansaequipment.com.au



T12

Features and Benefits




BUILT FOR DURABILITY

Manufactured from 304 stainless steel, the T12 is built for durability. A grit blasted and 2 pack painted chassis ensures longevity and that return on investment of the T12 outperforms expectations.



BUILT FOR COMFORT

The T12 is built for comfort and ease of use, with hydraulic drawbar suspension for the best ride possible as standard and the option of an automatic door eliminating any need to get out to adjust settings meaning a long days spreading becomes a pleasure.



PERFORMANCE AND RELIABILITY

The reliable design of the Southern Spreaders 760 chain conveyor feeds the spinners to produce a positive and consistent product feed of all materials in all conditions and terrain.



ISOBUS

Simply Plug and play, the Hansa ISOBUS control system is compatible with all ISOBUS compliant terminals and is variable rate ready as standard. This allows the operator to move the spreader from one machine to another with ease and no setup changes.



Inclusions & Options

		Inclusions ●	Optional ○
TYRES	650/65 R30.5 floatation tyres	●	
	520/85 R38 high load, high speed R1 tractor tyre		○
	650/65 R30.5 twin radial high speed, high load flotation tyre		○
TARP	900 gsm rollover tarp		○
LOAD CELLS	When selected with ISOBUS rate controller auto rate control is enabled		○
RATE CONTROLLER	ISOBUS (auto rate calibration) Hansa H7 controller (7" Touch screen)		○
SECTION CONTROL	Twin conveyor for headland and section control (available with H7 & ISOBUS rate controllers)		○
AXLE	Single series 150 ADR 10/335 (track options of 2,000mm, 2,200mm, 2,500mm & 3,000mm)	●	
BRAKES	Hydraulic		○

A full range of options are available upon request

Specifications

 **MAX PAYLOAD**
14,000 kg

 **SPREAD WIDTH**
Urea 36m / SSP 50m

CAPACITY
11,000L

TARE WEIGHT
4,450kg

LOADING HEIGHT
2,950mm

UREA CAPACITY
8,250kg

LIME CAPACITY
14,000kg

BIN LENGTH
4,000mm

OVERALL LENGTH
6,850mm

BIN WIDTH
2,300mm

STANDARD WHEEL TRACK
2,000mm

CONVEYER WIDTH
750mm wide

OIL FLOW
130L/min

WARRANTY
12 months

Hansa provides all information in good faith, and reserves all rights to alter/change specifications without notice. Purchasers must conduct their own enquiries to ensure that the products are suitable for their own particular purposes as all information is provided as an approximation and are to be used as a guide only. Photographs may show aftermarket or optional equipment that is available at extra cost. Hansa Precision Equipment Pty Ltd. Copyright 2020. ABN: 74 604 073 350

139 Learmonth St, Alfredton VIC
sales@hansaequipment.com.au
hansaequipment.com.au

