

T6



hansaequipment.com.au



T6

Features and Benefits



BUILT FOR DURABILITY

Manufactured from 304 stainless steel, the T6 is built for durability. A grit blasted and 2 pack painted chassis ensures longevity and that return on investment of the T6 outperforms expectations.



MAXIMUM UPTIME

The full hydraulic drive system featuring quality Permco Spinner motors and 2000 series conveyor motor means simply plugging in and going to work. Minimal grease points and required maintenance translates to simply getting on with the job.



PERFORMANCE AND RELIABILITY

The reliable design of the Southern Spreaders 760 chain conveyor feeds the spinners to produce a positive and consistent product feed of all materials in all conditions and terrain.



ISOBUS

Simply Plug and play, the Hansa ISOBUS control system is compatible with all ISOBUS compliant terminals and is variable rate ready as standard. This allows the operator to move the spreader from one machine to another with ease and no setup changes.



Inclusions & Options

Inclusions ●
Optional ○

TYRES	Harvest 18.4/30 R1 tractor tyres	●
	Harvest 600/60 R26.5 floatation tyre	○
	Michelin 600/55 R30.5 CargoBib flotation tyre	○
TARP	900 gsm rollover tarp	○
LOAD CELLS	When selected with load ISOBUS rate controller auto dynamic calibration is enabled	○
RATE CONTROLLER	ISOBUS (auto rate calibration)	○
	Hansa H5 controller (5" Touch screen)	○
	Hansa H7 controller (7" Touch screen)	○
SECTION CONTROL	Twin conveyor for headland and section control (available with H7 & ISOBUS rate controllers)	○
AXLE	Single series 100 ADR 10/335 (track options of 1,600mm, 1,800mm, 2,000mm, 2,200mm & 3,000mm)	●
BRAKES	Hydraulic	○

A full range of options are available upon request

Specifications

 **MAX PAYLOAD**
8,000 kg

 **SPREAD WIDTH**
Urea 36m / SSP 58m

CAPACITY
6,000L

TARE WEIGHT
2,250kg

LOADING HEIGHT
2,340mm

UREA CAPACITY
4,500kg

LIME CAPACITY
8,000kg

BIN LENGTH
3,400mm

OVERALL LENGTH
6,020mm

BIN WIDTH
2,300mm

STANDARD WHEEL TRACK
1,800mm

CONVEYER WIDTH
750mm wide

OIL FLOW
80L/min

WARRANTY
12 months

Hansa provides all information in good faith, and reserves all rights to alter/change specifications without notice. Purchasers must conduct their own enquiries to ensure that the products are suitable for their own particular purposes as all information is provided as an approximation and are to be used as a guide only. Photographs may show aftermarket or optional equipment that is available at extra cost. Hansa Precision Equipment Pty Ltd. Copyright 2022. ABN: 74 604 073 350

139 Learmonth St, Alfredton VIC
sales@hansaequipment.com.au
hansaequipment.com.au

